



## Eurotec Caseframes

#### **CUSTOM EUROTEC CASEFRAMES**

TecServ+ is the vehicle by which Verotec delivers its value added services. These fall within 5 main categories and are described below. When it comes to Eurotec caseframes, we've worked with many customers in the past to design, manufacture and help bring to market modified and custom versions of our standard products - a small selection of these are pictured below. If you have any special Eurotec caseframe requirements, please contact our sales office

#### **ENGINEERING SERVICES:**

- 0 Complete review of commercial, electro-mechanical, environmental and regulatory product requirements with customer.
- 0 Import of STEP, IGES, DWG & DXF file formats
- 0 Mechanical and electrical design using latest CAD software
- 0 3D Modelling to allow conceptual testing before production
- 0 Component selection from a vast library of parts

#### **MANUFACTURING SERVICES:**

- G Prototype / pre-production samples using small batch shop
- 0 Modification of standard catalogue products (including machining, CNC punching, laser cutting, painting & silk-screening)
- 0 Manufacture of custom / bespoke products (including fabrication, machining, CNC punching, plating, painting & silk-screening)
- 0 Assembly & kitting of components
- G Integration & mechanical / electrical testing of complex systems

#### **COMPLIANCE SERVICES:**

- 0 Validation of product design and/or specification
- 0 Advice on environment legislation (RoHS, Reach, Weee etc.)
- 0 In-house pre-compliance testing for CE marking (Safety, EMC)
- 0 Supply of product technical construction file
- 0 Testing & certification of a product at an approved test house (for EMC, shock & vibration, altitude, temperature, humidity etc.)

#### LOGISTICAL SERVICES:

- 0 Express manufacturing service for quick turnaround of urgent orders
- 0 Special / bespoke packaging for safe transport of goods
- 0 Scheduled orders (including JIT and KAN BAN systems)
- 0 Stock holding & distribution
- G Exporting (including export packaging, land/sea/air transportation, freight forwarding, customs documentation & shipping manifests)

#### **PROJECT MANAGEMENT SERVICES:**

- ß Initial project consultation
- 0 Capability and feasibility study
- 0 Estimation of project cost and leadtime
- 0 Management of design process (specification to validation)
- 0 Management of manufacturing process (prototype to production)
- Cost reduction programmes throughout product life cycle





Customised 3U/4U, 19" rack-mounting Eurotec caseframe with integrated VME backplane & guides - railway application.



painted anthracite with special vent patterns top and bottom - instrumentation application



Customised 3U, 60HP Eurotec caseframe specially painted and assembled with backplane, guides and hardware - VoiP application.



UK 🕾 +44 (0)2380-246900 sales@verotec.co.uk

US 1-603-82I-992I sales@verotec.us

## Eurotec Caseframes

#### EUROTEC CASEFRAMES

The Eurotec Caseframe is designed for applications that require the mounting / housing of Eurocard-style electronics (cards or modules) in either a 19" rackmount, desktop or portable formfactor. A step up from a standard subrack, its design requires no external housing, and offers optional EMC protection along with the integration of cooling fans and power supplies in a self contained, attractive unit. Top and bottom covers are easily removed for system building and servicing requirements.

#### FEATURES:

- Desk top, 19" Rack mounting or portable
  - EMC Upgrade
- Easy access for servicing
- Attractive appearance
- 3U and 6U Eurocard form factors
- 3 overall height variants for each size
- 3 overall depth variations for each size
- 2 card connection variants
- Thermal management
- Chassis system compatibility
- KM6-II compatible

#### ORDERING

The Caseframe is supplied in assembled form. It should be selected by size (ie. height and depth), style and, similar to KM6-II subracks, by rear extrusion type (either backplane mounting or DIN 41612 connector mounting). 240mm deep versions are assembled to suit 160mm cards / modules whilst 360mm & 480mm versions are assembled to suit 220mm cards / modules.

Note that 220mm guides will not fit in a 240mm caseframe.

#### ACCESSORIES

The use of standard subrack extrusions means that the Eurotec Caseframe can accept most accessories from our standard KM6-II subrack range, including card guides, front panels, divider kits, plug-in units, and emc screening kits. The Caseframes are also compatible with our versatile chassis system which permits the mounting of additional components – eg power supplies, mechanical assemblies and cable management. These items are not listed here – details can be found in the KM6-II subracks and KM6-II Front Panels sections.

A number of specific Eurotec Caseframe accessories are also available including front trims, handles, tilt feet, fan trays and rear panels, allowing the requirements of many applications to be met with standard off-the shelf parts.

#### **ELECTRICAL CONTINUITY**

Careful attention to the masking of painted areas, together with the inherent conductivity of the basic subrack, provides excellent electrical conductivity of the complete assembly. Testing was carried out according to B57002/ IEC 60950.

#### **COLOURS**


Two paint colours are used as standard: Light Grey RAL 7035 and Window Grey RAL 7040. Finish is epoxy powder coat.

#### **EMC PERFORMANCE**

Tests on a 3U/4U Eurotec caseframe were carried out in our screened facility according to a standard procedure. The procedure was based on MIL-STD 285 using automated frequency control and data recording. Results are shown below for units tested three forms:



EurotecCaseframes CASEFRAME RF SHIELDING



a) In basic form, with flat anodised front and rear 84HP panels;
b) With 50% BeCu RFI fingers atfront and rear interfaces and 84HP EMC panels;
c) As b), but with 100% BeCu fingers.

The overall EMC performance of the Eurotec Caseframe can be improved in a number of different ways, depending on which size you have. Beryllium copper, self-adhesive, RFI finger strips can be fitted to all units and should be placed at the front and rear interfaces. They are supplied in single lengths of 381mm and consist of 60 fingers. They should be spaced evenly along the required surfaces with more fingers producing better performance.

The 3U/4U, 3U/5U, 6U/7U & 6U/8U Eurotec Caseframes can also be fitted with full EMC screening kits to obtain a high level of screening. The kits include a plain or ventilated top and bottom cover which can cover either the board area or the whole subrack area, depending on whether a full-width backplane is being used and what your specific requirements are.

Finally, 3U/6U x 84HP EMC closing panels are available in fixed or hinged versions for fitting to the front and rear of the subrack area. For full details of the EMC screening kits and closing panels, please refer to the "EMC Conversion" section of the "KM6-II Subracks and Accessories" section.



3U/4U & 6U Rackmount Eurotec Caseframes

UK 🕾 +44 (0)2380-246900 sales@verotec.co.uk US<sup>®</sup>+I-603-82I-992I sales@verotec.us

### Eurotec Caseframes







19" Rack

#### **CASEFRAME STYLES**

The Eurotec Caseframe is available in either a desktop, 19" rackmount or portable style to suit a number of different application environments.

**Desktop** – with front trims giving a neat appearance and with fold down feet fitted at the front and complimentary non-slip feet at the rear. Included is a kit of 4 x 10mm round adhesive rubber bumper stops that can be used as an alternative to the feet. These should be positioned in the depressions in the bottom cover.

**Rack Mount -** with mounting angles at the front to provide fixings within a 19" rack system to IEC 297.

**Portable –** with a stylish, locking, swing handle for carrying and providing a front support (limited to 30Kg load in any position).

#### **CASEFRAME SIZES**

The Eurotec Caseframe is available in 3 depths of 240, 360 & 480mm internally. Standard eurocard heights of 3U & 6U are catered for, each with 3 variations available, providing a range of 6 heights. (Refer to page 7 for pictorial views)

**3U & 6U** Caseframes are true height enclosures with close fitting unventilated top & bottom covers.

**3U/4U & 6U/7U** Caseframes are fitted with ½U high covers ventilated on one edge which can be mounted front or rear (standard frames will be assemble bottom - front vented & top - rear vented)

**3U/5U & GU/8U** Caseframes are fitted with  $\frac{1}{2}$ U high ventilated top cover and a  $\frac{1}{2}$ U high bottom fan tray cover closed at the front with a ventilated cover plate

The ½U high covers are reversible. Standard caseframes will be assembled bottom - front vented & top - rear vented. The units with ½U and 1½U covers are EMC upgradeable without the addition of subrack EMC covers but to a lesser degree of shielding due to the vent slot sizes.

#### **CASEFRAME CONNECTION STYLES**

EurotecCaseframes are available in 2 card connection styles.

#### **Backplane mounting**

With extruded rails top & bottom to mount a backplane (motherboard).


The 6U high has the facility to mount a centre tie bar. Tapped strips are fitted front x 2, backplane x 1 and rear x 1 at top & bottom positions


#### **DIN 41612 connector mounting**

With extruded rails top & bottom (& centre on 6U) for direct mounting of connectors in the DIN 41612 series. Tapped strips are fitted front x 2, and rear x 1 at top & bottom position









Height	Debiu	Desktop	Mount	Portable
3u	240	738-4000630	738-4000670	738-4000710
	360	738-4000631	738-4000671	738-4000711
	480	738-4000632	738-4000672	738-4000712
3u/4u	240	738-4000633	738-4000673	738-4000713
	360	738-4000634	738-4000674	738-4000714
	480	738-4000635	738-4000675	738-4000715
3u/5u	240	738-4000636	738-4000676	738-4000716
	360	738-4000637	738-4000677	738-4000717
	480	738-4000638	738-4000678	738-4000718
	240	738-4000639	738-4000679	738-4000719
6u	360	738-4000640	738-4000680	738-4000720
	480	738-4000641	738-4000681	738-4000721
6u/7u	240	738-4000642	738-4000682	738-4000722
	360	738-4000643	738-4000683	738-4000723
	480	738-4000644	738-4000684	738-4000724
6u/8u	240	738-4000645	738-4000685	738-4000725
	360	738-4000646	738-4000686	738-4000726
	480	738-4000647	738-4000687	738-4000727

#### DIN 41612 UNITS:

BACKPLANE MOUNTING UNITS:

Height	Depth	Desktop	19" Rack Mount	Portable
3u	240	738-4000648	738-4000688	738-4000728
	360	738-4000649	738-4000689	738-4000729
	480	738-4000650	738-4000690	738-4000730
3u/4u	240	738-4000651	738-4000691	738-4000731
	360	738-4000652	738-4000692	738-4000732
	480	738-4000653	738-4000693	738-4000733
3u/5u	240	738-4000654	738-4000694	738-4000734
	360	738-4000655	738-4000695	738-4000735
	480	738-4000656	738-4000696	738-4000736
	240	738-4000657	738-4000697	738-4000737
6u	360	738-4000658	738-4000698	738-4000738
	480	738-4000659	738-4000699	738-4000739
	240	738-4000660	738-4000700	738-4000740
6u/7u	360	738-4000661	738-4000701	738-4000741
	480	738-4000662	738-4000702	738-4000742
6u/8u	240	738-4000663	738-4000703	738-4000743
	360	738-4000664	738-4000704	738-4000744
	480	738-4000665	738-4000705	738-4000745

3.04 VEROTEC Electronics Packaging UK 🕾 +44 (0)2380-246900 sales@verotec.co.uk US®+I-603-82I-992I sales@verotec.us

## Eurotec Caseframes : Accessories

#### **EUROTEC CASEFRAME ACCESSORIES**

A wide range of compatible KM6-II accessories can be found in the Subracks / Front Panel brochures / sections and include guides, front panels, modules and chassis system etc. In addition to these, the following specific accessories are also available ensuring the requirements of many applications can be met with standard off-the shelf parts

#### **DESKTOP CONVERSION**

Standard Eurotec Caseframes are 84HP wide and the Rack Mounted Unit may be converted to a Desk Top unit by replacing the rack mounting angles with a set of front trims. Select by the overall height. Front Trims are supplied in Pairs

#### **19" RACK MOUNT CONVERSION**

Standard Eurotec Caseframes are 84HP wide and can be rack mounted by replacing the desktop trim angles with a set of rack mounting angles. Select by the overall height. Rack mounting angles are supplied in packs of two

#### **RACKMOUNT ANGLES WITH HANDLES**

The Rack Mount angle / handle kit may be added to either the desktop or rackmount Eurotec caseframes, should this functionality be required. Select by the overall height and note that the kit replaces either the trim or rack angle currently fitted. Supplied as a pair.

#### **REAR PANELS - ALUMINIUM**

The rear aperture permits the use of any standard IEC 297-3 panels, a selection of which can be found in the "KM6-II Front Panel" section of the brochure. Offered here are standard 3U and 6U x 84HP anodized aluminium panels complete with fixing screws

#### **VENTED REAR PANELS**

The Eurotec Caseframes have dedicated, painted, ventilated rear panels to complement the unit in either 3U or 6U height. Panels are supplied with fixing screws.

#### FAN REAR PANELS

The Eurotec Caseframes have dedicated, painted, fan rear panels punched to accept 3 x 80mm fans, to complement the unit in either 3U or 6U height. Panels are supplied with fixing screws.

#### **ORDERING INFORMATION**

Description	Size	Order Code			
	3U	738-4000758			
Dealter	3U/4U	738-4000759			
Desktop - Front Trim Kit -	3U/5U	738-4000760			
Pack of 2	6U	738-4000761			
Pack of 2	6U/7U	738-4000762			
-	6U/8U	738-4000763			
	3U	738-4000764			
	3U/4U	738-4000765			
Rack Mount kit	3U/5U	738-4000766			
Pack of 2	6U	738-4000767			
	6U/7U	738-4000768			
-	6U/8U	738-4000769			
	3U	738-4001070			
Rack Mount Angle with	3U/4U	738-4001071			
Handle Kit	3U/5U	738-4001072			
Pack of 2	6U	738-4001073			
-	6U/7U	738-4001074			
	6U/8U	738-4001075			
Standard 84HP Aluminium	3U	957-236065			
Panel Panel + fixings	6U	957-236073			
Ventilated Rear Panel	3U	738-4000770			
Panel + fixings	6U	738-4000771			
Fan Rear Panel	3U	738-4000772			
Panel + fixings	6U	738-4000773			




Desktop conversion





19" rack mount conversion









UK 🕾 +44 (0)2380-246900 sales@verotec.co.uk US 🕾 + I-603-82I-992I sales@verotec.us

## Eurotec Caseframes : Accessories

#### DROP IN FAN TRAY

The bottom cover of the 3U/5U & 6U/8U versions, which is 1½U high, will accept a drop-in fan tray, which draws air through the ventilated front, fitted with an inlet filter retained by the outer front cover. The tray has three positions for 120mm fans and is available for 160mm & 220mm card depths. Unused fan positions can be filled with blanking plates. Contents of kit: 1 fan tray, filter, terminal block and fixings. (Refer to page 8 for pictorial view) Order separately: fans and wiring.

#### **TILT FOOT FACILITY**

The Eurotec Casframes have a modified bottom panel which enables the user to fit these feet without any need to drill the panel. It is thus possible to provide a tilt facility at low cost. The feet are fitted by means of self-tapping screws, but it should be noted that if used with a rack mounting Caseframe they will intrude into the 'U' below. Supplied as a set of four feet, with fixings. (Note: Tilt feet are fitted as standard on the desktop version) Material: UL94-V0 rated ABS Colour: grey -

#### **1½U BLIND FRONT COVER**

The 3U/5U and 6U/8U Eurotec Caseframes are fitted with a filter element and vented front panel as standard in the bottom 1.5U of the unit. Should this air-intake not be required, the vented panel may be replaced with a blind front cover. (Refer to page 8 for pictorial view)

#### RUBBER FEET

The bottom cover of the Eurotec Caseframe contains 4 x depressions where a 10mm rubber adhesive bumper stop can be positioned, should the tilt feet not be required. Supplied as a set of 4. (Note: Supplied as standard on the desktop version)"

#### HIGHLIGHT STRIPS

Self-adhesive, coloured strips are available to provide coloured highlights along the side of the Eurotec Caseframe. They are available in blue or grey and are supplied singly in 1 metre lengths

#### EMC SCREENING

Beryllium copper, self-adhesive, RFI finger strips can be fitted to all units and should be placed at the front and rear interfaces to improve EMC performance. They are supplied in single lengths of 381mm and consist of 60 fingers.


#### EUROTECCASEFRAME ACCESSORIES

A wide range of compatible KM6-II accessories can be found in the Subracks / Front Panel brochures / sections and include guides, front panels, modules and chassis system etc. In addition to these, the following specific accessories are also available ensuring the requirements of many applications can be met with standard off-the shelf parts

#### **ORDERING INFORMATION**

**/ERO**][(

Description	Size	Order Code
Drop-in Fan Tray	160 Deep	738-4000774
Tray + accessories	220 Deep	738-4000775
1.5U Blind Panel	3U/5U & 6U/8U	738-4000776
Tilt Foot Kit - Grey	All	50-54602
Rubber Feet (Pack 4)	All	50-4001069
Highlight Strips	Grey	738-4001750
1M length	Blue	738-4001751
BeCu RFI Finger Strip (381mm)	All	930-238243




Drop in fan tray





Highlight Strips






Eurotec

3.06

US 🕾 + I-603-82I-992I sales@verotec.us



# Eurotec aseframes

0 M

### All dimensions in mm




UK 🕾 +44 (0)2380-246900 sales@verotec.co.uk

FR 🕾 +33 (0)3-444-514-60 sales@verotec.fr

3.07

## Eurotec Caseframe : Dimensions




**INTERNAL DEPTH** 

VEROTE **Electronics Packaging** 

3.08

UK 🕾 +44 (0)2380-246900 sales@verotec.co.uk

US 1-603-82I-992I sales@verotec.us



All dimensions in mm

VEROTEC Electronics Packaging UK 🕾 +44 (0)2380-246900 sales@verotec.co.uk US 🕾 + I-603-82I-992I sales@verotec.us FR 🕾 +33 (0)3-444-514-60 sales@verotec.fr

3.09